NSN 5905-00-299-7995

Inductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-299-7995

## SEGN #105.0 Electrical Resistance: 188.000 ohms Resistance Tolerance in Percent: -0.100/#-0.100 Ambient Tempurature in Deg Celsius At Full Rated Power: 66.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 121.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 40.0/46.0.0 10.0/46.0.0 Inclosure Method: Hermelically sealed Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Batween 1.986 inches and 2.031 inches Body Length: Between 0.399 inches and 0.391 inches Body Length: Between 0.399 inches and 1.031 inches Power Dissipation Rating in Watts: 0.250 frea air Sylve Designator: Avial terminal each end Test Data Document: Every Specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Na	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Electrical Resistance: 188.000 ohms Resistance Tolerance In Percent:	
Resistance Tolerance in Percent: -0.100/40.100 Ambient Tempurature in Deg Celsius At Full Rated Power: 66.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 121.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -0.0/+60.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.959 inches and 2.031 inches Body Diameter: Bottween 0.359 inches and 0.391 inches Body Diameter: Between 0.359 inches and 1.031 inches Power Dissipation Rating in Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 64959-ga10684 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: No Unit Of Measure: - Demilitarization: No Filig:	
Resistance Tolerance In Percent: -0.100/+0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 6.6.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 121.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: +0.0/+6.0.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.969 inches and 2.031 inches Body Diameter: Between 0.359 inches and 0.391 inches Body Length: Between 0.969 inches and 1.031 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 64959-9410684 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheff Life: No Unit Of Measure: Demilitarization: No Filig:	
-0.100/40.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 66.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 121.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: +0.0/+60.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1,969 inches and 2,031 inches Body Diameter: Between 0,359 inches and 0.391 inches Body Length: Between 0,969 inches and 1.031 inches Power Dissipation Rating In Watts: 0,250 free air Style Designator: Axial terminal each end Test Data Document: 64959-ga10684 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Na Unit Of Measure:	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 121.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: +0.0/+60.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.969 inches and 2.031 inches Body Length: Between 0.359 inches and 0.391 inches Body Length: Between 0.999 inches and 1.031 inches Power Dissipation Rating in Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheff Life: Na Unit Of Measure: Demilitarization: No Filg:	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 121.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: +0,0/+60.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.969 inches and 2.031 inches Body Diameter: Between 0.359 inches and 0.391 inches Body Diameter: Between 0.959 inches and 1.031 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: Avial designation, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: — Demilitarization: No Filg:	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 121.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: +0.0/+60.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1,969 inches and 2.031 inches Body Diameter: Between 0,359 inches and 0,391 inches Body Length: Between 0,359 inches and 1,031 inches Body Length: Setween 1,969 inches and 1,031 inches Power Dissipation Rating In Watts: 0,250 free air Style Designator: Axial terminal each end Test Data Document: 64959-ga10684 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	
Tempurature Range Of Tempurature Coefficient In Deg Celsius: +0.0+60.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.969 inches and 2.031 inches Body Diameter: Between 1.969 inches and 0.391 inches Body Dength: Between 0.969 inches and 1.031 inches Body Length: Between 0.969 inches and 1.031 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 64959-ga 10684 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Tempurature Range Of Tempurature Coefficient In Deg Celsius: +0.0/+60.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.969 inches and 2.031 inches Between 1.969 inches and 2.031 inches Between 0.359 inches and 0.391 inches Between 0.359 inches and 0.391 inches Bedy Diameter: Between 0.959 inches and 1.031 inches Bedy Length: Between 0.969 inches and 1.031 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 64959-ga10684 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	
+0.0/+60.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.969 inches and 2.031 inches Body Diameter: Between 0.359 inches and 0.391 inches Body Diameter: Between 0.359 inches and 1.031 inches Body Length: Between 0.969 inches and 1.031 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 64959-ga10684 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	
Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.969 inches and 2.031 inches Body Diameter: Between 0.359 inches and 0.391 inches Body Length: Between 0.969 inches and 1.031 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 64959-9a10684 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	
Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.969 inches and 2.031 inches Body Diameter: Between 0.359 inches and 0.391 inches Body Length: Between 0.969 inches and 1.031 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 64959-ga10684 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.969 inches and 2.031 inches Body Diameter: Between 0.359 inches and 0.391 inches Body Length: Between 0.969 inches and 1.031 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 64959-ga10684 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Wire lead Reliability Indicator: Not established Terminal Length: Between 1.969 inches and 2.031 inches Body Diameter: Between 0.359 inches and 0.391 inches Body Length: Between 0.969 inches and 1.031 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 64959-ga10684 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Reliability Indicator: Not established Terminal Length: Between 1.969 inches and 2.031 inches Body Diameter: Between 0.359 inches and 0.391 inches Body Length: Between 0.969 inches and 1.031 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 64959-ga10684 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Note stablished Terminal Length: Between 1.969 inches and 2.031 inches Body Diameter: Between 0.359 inches and 0.391 inches Body Length: Between 0.969 inches and 1.031 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 64959-ga10684 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Reliability Indicator:
Between 1.969 inches and 2.031 inches Body Diameter: Between 0.359 inches and 0.391 inches Body Length: Between 0.969 inches and 1.031 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 64959-ga10684 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Between 0.359 inches and 0.391 inches Body Length: Between 0.969 inches and 1.031 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 64959-ga10684 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Terminal Length:
Between 0.359 inches and 0.391 inches Body Length: Between 0.969 inches and 1.031 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 64959-ga10684 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Between 1.969 inches and 2.031 inches
Between 0.969 inches and 1.031 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 64959-ga10684 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Body Diameter:
Between 0.969 inches and 1.031 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 64959-ga10684 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Between 0.359 inches and 0.391 inches
Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 64959-ga10684 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Body Length:
O.250 free air Style Designator: Axial terminal each end Test Data Document: 64959-ga10684 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Between 0.969 inches and 1.031 inches
Style Designator: Axial terminal each end Test Data Document: 64959-ga10684 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Power Dissipation Rating In Watts:
Axial terminal each end Test Data Document: 64959-ga10684 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.250 free air
Test Data Document: 64959-ga10684 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Style Designator:
64959-ga10684 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Axial terminal each end
excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Test Data Document:
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	64959-ga10684 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.
N/a Unit Of Measure: Demilitarization: No Fiig:	excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
A001a0	Fiig:
	A001a0