NSN 5905-00-307-3965

Inductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-307-3965				
Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:				
-30.0/+30.0				
Electrical Resistance:				
5.490 kilohms				
Resistance Tolerance In Percent:				
-1.000/+1.000				
Ambient Tempurature In Deg Celsius At Full Rated Power:				
25.0				
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:				
275.0				
Tempurature Range Of Tempurature Coefficient In Deg Celsius:				
-55.0/+275.0				
Inclosure Method:				
Encased				
Terminal Type:				
Tab, solder lug				
Reliability Indicator:				
Established				
Reliability Failure Rate Level In Percent:				
0.010				
Terminal Length:				
Between 0.376 inches and 0.500 inches				
Body Length:				
Between 1.876 inches and 2.000 inches				
Body Width:				
Between 0.532 inches and 0.656 inches				
Body Height:				
Between 0.594 inches and 0.656 inches				
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:				
Between 1.552 inches and 1.572 inches				
Power Dissipation Rating In Watts:				
10.000 free air				
Terminal Width:				
0.140 inches				
Mounting Hole Size:				
Between 0.120 inches and 0.130 inches				
Cubic Measure (non-core):				
0.719 cubic inches				
Unpackaged Unit Weight:				

32.0 grams

Style Designator:

Axial terminal (s)

NSN 5905-00-307-3965

Inductive Wire Wound Fixed Resistor - Page 2 of 2



Test Data Document:

81349-mil-r-39009 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mi	I-r-39009/1	government s	specification
010101111		9010111110111	poomoanom

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A001a0