

View Online at <https://aerobasegroup.com/nsn/5905-00-307-4323>

Section Quantity:

2

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

First Flat Length:

0.630 inches

Flat Height:

0.217 inches

Body Diameter:

1.160 inches

Shaft Diameter:

0.250 inches

Shaft Length:

1.380 inches

Mounting Bushing Length:

0.500 inches

Body Length:

1.270 inches

Shaft Style:

Round, flatted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

312.0

Maximum Starting Torque:

9.00 inch-ounces

Maximum Running Torque:

1.00 inch-ounces

Maximum Stop Torque:

192.00 inch-ounces

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

0.531 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

75.000 ohms all sections

Rotary Actuator Travel In Angular Deg:

312.0

Resistance Temperature Characteristic Range Per Section In Percent:

+0.0 to 4.5 -55 degrees celsius all sections and +0.0 to 2.5 -25 degrees celsius all sections and +0.0 to 1.5 0 degrees celsius all sections and -1.5 to 1.5 85 degrees celsius all sections and +0.0 to 3.5 120 degrees celsius all sections

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 all sections

Power Dissipation Rating Per Section In Watts:

2.25 free air 1st section

Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 all sections

Actuator Travel Control Feature:

Stops

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 all sections

Standard Taper Curve Per Section:

A all sections

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0