NSN 5905-00-312-3958

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-312-3958 **Section Quantity: Body Style:** Rectangular **Reliability Indicator:** Not established **Body Length:** 0.218 inches **Body Width:** 0.593 inches **Body Height:** 0.733 inches **Actuator Type:** Flush drive with slot-hole **Effective Electrical Rotation In Deg Angular Rotation:** 260.0 **Terminal Location:** Lower adjacent side single row **Mounting Method:** Tab **Features Provided:** Grounded contact arm **Electrical Resistance Per Section:** 1.5 kilohms single section **Rotary Actuator Travel In Angular Deg:** 260.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 85.0 single section **Power Dissipation Rating Per Section In Watts:** 0.2 free air single section **Resistance Tolerance Per Section In Percent:** -20.0 to 20.0 single section **Actuator Travel Control Feature:** Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 55.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 2 tab, solder lug Shelf Life:

N/a

NSN 5905-00-312-3958

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A002a0