NSN 5905-00-312-9889

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-312-9889

| Section Quantity: |
|---|
| 1 |
| Body Style: |
| Cylindrical bushing mounted |
| Overall Length: |
| 1.870 inches |
| Body Diameter: |
| 1.220 inches |
| Shaft Diameter: |
| 0.250 inches |
| Shaft Length: |
| 1.250 inches |
| Body Length: |
| 0.620 inches |
| Overall Diameter: |
| 1.750 inches |
| Shaft Style: |
| Round, slotted |
| Contact Arm Electrical Off Position: |
| Fully ccw |
| Actuator Type: |
| Single shaft |
| Effective Electrical Rotation In Deg Angular Rotation: |
| Between 290.0 and 305.0 |
| Maximum Starting Torque: |
| 6.00 inch-ounces |
| Maximum Stop Torque: |
| 128.00 inch-ounces |
| Nonturn Device Location: |
| At 9 oclock |
| Nonturn Device Radius: |
| 0.531 inches |
| Screw Thread Diameter: |
| 0.375 inches |
| Screw Thread Series Designator: |
| Unef |
| Screw Thready Qty Per Inch (tpi): |
| 32.0 |
| Terminal Location: |
| Radially positioned over less than half the circumference |
| Mounting Method: |

Standard bushing

NSN 5905-00-312-9889

A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



| Electrical Resistance Per Section: |
|---|
| 35.000 ohms single section |
| Rotary Actuator Travel In Angular Deg: |
| Between 290.0 and 305.0 |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: |
| 105.0 single section |
| Power Dissipation Rating Per Section In Watts: |
| 2.0 free air single section |
| Resistance Tolerance Per Section In Percent: |
| -10.0 to 10.0 single section |
| Actuator Travel Control Feature: |
| Stops |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: |
| 40.0 single section |
| Standard Taper Curve Per Section: |
| A single section |
| Test Data Document: |
| 81349-mil-r-19-2 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Terminal Type And Quantity: |
| 3 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |