NSN 5905-00-315-2031

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-315-2031

Ocasian Occanition
Section Quantity:
Body Style:
Rectangular
Reliability Indicator:
Not established
Overall Length: 0.547 inches
Terminal Length: 0.187 inches
Overall Height:
0.312 inches
Overall Width:
0.315 inches
Body Length: 0.375 inches
Body Width: 0.235 inches
Body Height:
0.312 inches
Actuator Type:
Flush drive with slot-hole
Center To Center Distance Between Terminals:
0.200 inches
Terminal Location:
Upper adjacent side two rows
Mounting Method:
Terminal
Electrical Resistance Per Section:
1.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
1440.0
Center To Center Distance Between Center Terminal And Outside Terminal:
0.100 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-100.0 to 100.0 single section
Power Dissipation Rating Per Section In Watts:
0.5 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section

NSN 5905-00-315-2031

A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Actuator Travel Control Feature:	
Clutch	
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:	
85.0 single section	
Standard Taper Curve Per Section:	
A single section	
Terminal Type And Quantity:	
3 pin	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	