NSN 5905-00-317-6013

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-317-6013 **Section Quantity:** 1 **Body Style:** Rectangular bushing mounted **Reliability Indicator:** Not established **Overall Length:** 1.530 inches **Terminal Length:** 6.000 inches **Overall Height:** 0.400 inches **Overall Width:** 0.300 inches **Mounting Hole Diameter:** 0.093 inches **Shaft Diameter:** 0.325 inches **Shaft Length:** 1.000 inches **Mounting Bushing Length:** 0.280 inches **Body Length:** 1.250 inches **Body Width:** 0.325 inches **Body Height:** 0.325 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Maximum Starting Torque:** 5.00 inch-ounces **Mounting Facility Quantity: Terminal Location:** Rear end

Mounting Method: Unthreaded hole

Electrical Resistance Per Section:

500.000 ohms single section

NSN 5905-00-317-6013

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-10.0 to 10.0 single section

Power Dissipation Rating Per Section In Watts:

0.5 free air single section

Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0