## NSN 5905-00-317-9068

Noninductive Wire Wound Fixed Resistor - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5905-00-317-9068                |  |  |  |
|--|--|--|--|
| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:                |  |  |  |
| -50.0/+50.0  |  |  |  |
| Electrical Resistance:   |  |  |  |
| 16.900 ohms  |  |  |  |
| Resistance Tolerance In Percent:   |  |  |  |
| -1.000/+1.000  |  |  |  |
| Ambient Tempurature In Deg Celsius At Full Rated Power:                      |  |  |  |
| 25.0   |  |  |  |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:              |  |  |  |
| 275.0  |  |  |  |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius:                 |  |  |  |
| -55.0/+275.0   |  |  |  |
| Inclosure Method:  |  |  |  |
| Encased  |  |  |  |
| Terminal Type:   |  |  |  |
| Tab, solder lug  |  |  |  |
| Reliability Indicator:   |  |  |  |
| Established  |  |  |  |
| Reliability Failure Rate Level In Percent:                                   |  |  |  |
| 0.010  |  |  |  |
| Terminal Length:   |  |  |  |
| Between 0.376 inches and 0.500 inches  |  |  |  |
| Body Length:   |  |  |  |
| Between 1.876 inches and 2.000 inches  |  |  |  |
| Body Width:  |  |  |  |
| Between 0.532 inches and 0.656 inches  |  |  |  |
| Body Height:   |  |  |  |
| Between 0.594 inches and 0.656 inches  |  |  |  |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: |  |  |  |
| Between 1.552 inches and 1.572 inches  |  |  |  |
| Power Dissipation Rating In Watts:   |  |  |  |
| 10.000 free air  |  |  |  |
| Terminal Width:  |  |  |  |
| 0.140 inches   |  |  |  |
| Mounting Hole Size:  |  |  |  |
| Between 0.120 inches and 0.130 inches  |  |  |  |
| Cubic Measure (non-core):  |  |  |  |
| 0.719 cubic inches   |  |  |  |
| Unpackaged Unit Weight:  |  |  |  |

35.0 grams

Style Designator:

Axial terminal (s)

## NSN 5905-00-317-9068

Noninductive Wire Wound Fixed Resistor - Page 2 of 2



## **Test Data Document:**

81349-mil-r-39009 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Specification Data:**

| 81349-mil-r-39009/2 | government s | pecification |
|---------------------|--------------|--------------|
|---------------------|--------------|--------------|

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A001a0