NSN 5905-00-320-0648

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-320-0648 **Section Quantity: Reliability Indicator:** Not established **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 3384.0 Mechanical Backlash In Deg Angular Rotation: 0.1 **Screw Thread Diameter:** 0.190 inches **Screw Thread Series Designator:** Unc Screw Thready Qty Per Inch (tpi): 24.0 **Mounting Facility Quantity: Terminal Location:** Radially positioned over more than half the circumference **Mounting Method:** Threaded hole **Features Provided:** Humidity proof **Electrical Resistance Per Section:** 4.75 kilohms single section **Rotary Actuator Travel In Angular Deg:** 3384.0 **Function Conformity Tolerance Per Section:** -0.10/+0.10 single section **Function Conformity Per Section:** Single section zero based linearity **Resistance Tolerance Per Section In Percent:** -1.0/+1.0 single section **Actuator Travel Control Feature:** Stops **Function Characteristic Per Section:** Single section linear **Terminal Type And Quantity:**

3 tab, solder lug

NSN 5905-00-320-0648

Precision Wire Wound Variable Resistor - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Domilitarization

Demilitarization:

No

Fiig:

A002a0