NSN 5905-00-320-6509

Film Fixed Resistor - Page 1 of 1

A001a0



View Online at https://aerobasegroup.com/nsn/5905-00-320-6509

| Tempurature Coefficient Of Resistance in Ppm Per Deg Ceisius: |
|--|
| -25.0/+25.0 |
| Electrical Resistance: |
| 1.000 kilohms |
| Resistance Tolerance In Percent: |
| -0.100/+0.100 |
| Ambient Tempurature In Deg Celsius At Full Rated Power: |
| 125.0 |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: |
| 175.0 |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius: |
| -55.0/+175.0 |
| Inclosure Method: |
| Encapsulated |
| Terminal Type: |
| Wire lead |
| Reliability Indicator: |
| Established |
| Reliability Failure Rate Level In Percent: |
| 0.001 |
| Body Diameter: |
| 0.065 inches |
| Body Length: |
| 0.150 inches |
| Power Dissipation Rating In Watts: |
| 0.050 free air |
| Special Features: |
| Nuclear hardness critical items |
| Nuclear Hardness Critical Feature: |
| Hardened |
| Style Designator: |
| Axial terminal each end |
| Test Data Document: |
| 81349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fila: |