

View Online at <https://aerobasegroup.com/nsn/5905-00-320-9879>

Section Quantity:

2

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

1.5000 inches

Pilot Length:

0.0620 inches

Undercut Diameter:

1.656 inches

Undercut Width:

0.0620 inches

Body Diameter:

1.781 inches

Shaft Diameter:

0.250 inches

Shaft Length:

1.062 inches

Body Length:

1.750 inches

Mounting Lip Diameter:

1.7810 inches

Mounting Lip Depth:

0.0620 inches

Shaft Style:

Round

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

320.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Clamp ring

Electrical Resistance Per Section:

50.0 kilohms 1st section

Rotary Actuator Travel In Angular Deg:

360.0

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

85.0 all sections

Power Dissipation Rating Per Section In Watts:

3.0 free air all sections

Resistance Tolerance Per Section In Percent:

-3.0 to 3.0 all sections

Actuator Travel Control Feature:

Continuous motion

Temperature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:

-20.0 to 20.0 all sections

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

25.0 all sections

Standard Taper Curve Per Section:

A all sections

Terminal Type And Quantity:

6 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0