

View Online at <https://aerobasegroup.com/nsn/5905-00-320-9882>

Section Quantity:

3

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

1.5000 inches

Pilot Length:

0.0620 inches

Undercut Diameter:

1.500 inches

Undercut Width:

0.0620 inches

Body Diameter:

1.620 inches

Shaft Diameter:

0.250 inches

Shaft Length:

1.000 inches

Body Length:

2.531 inches

Mounting Lip Diameter:

1.6200 inches

Mounting Lip Depth:

0.0620 inches

Shaft Style:

Round

Shaft Bearing Type:

Ball

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

320.0

Shaft Runout:

0.001 inches

Lateral Runout:

0.001 inches

Pilot Diameter Runout:

0.00100 inches

Shaft Radial Play:

0.001 inches

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Clamp ring

Electrical Resistance Per Section:

69.0 percent, rated amperes c and better select

Rotary Actuator Travel In Angular Deg:

360.0

Function Conformity Tolerance Per Section:

-0.25/+0.25 all sections

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

80.0 all sections

Power Dissipation Rating Per Section In Watts:

3.0 free air all sections

Function Conformity Per Section:

All sections independent linearity

Resistance Tolerance Per Section In Percent:

-5.0/+5.0 3rd section

Actuator Travel Control Feature:

Continuous motion

Function Characteristic Per Section:

All sections linear

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

25.0 all sections

Terminal Type And Quantity:

9 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0