## NSN 5905-00-321-1295

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-321-1295

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Body Diameter:
1.281 inches
Mounting Bushing Length:
0.500 inches
Body Length:
0.750 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
300.0
Nonturn Device Location:
At 11: 00 oclock
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
75.0 ohms single section
Rotary Actuator Travel In Angular Deg:
300.0
Fixed Tap Quantity Per Section:
1 single section
Resistance Tolerance Per Section In Percent:
-20.0 to 20.0 single section
Actuator Travel Control Feature:
Stops
Standard Taper Curve Per Section:

A single section

## NSN 5905-00-321-1295

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Termi	nal T	ype And	Quantity
4 tab.	sold	er lug	

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0