NSN 5905-00-321-6838

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-321-6838

Section Quantity:
1
Body Style:
Cylindrical servo mounted
Reliability Indicator:
Not established
Pilot Diameter:
Between 0.96830 inches and 0.96880 inches
Pilot Length:
0.06200 inches
Overall Length:
1.890 inches
Undercut Width:
0.05700 inches
Shaft Diameter:
Between 0.124 inches and 0.125 inches
Mounting Lip Diameter:
1.06200 inches
Mounting Lip Depth:
0.06200 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Mounting Method:
Clamp ring
Features Provided:
Nonmetallic shaft
Electrical Resistance Per Section:
10.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
360.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Power Dissipation Rating Per Section In Watts:
0.25 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Continuous motion
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
110.0 single section

NSN 5905-00-321-6838

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Terminal Type And Quantity:
2 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0