

View Online at <https://aerobasegroup.com/nsn/5905-00-321-7092>

**Reliability Indicator:**

Not established

**Terminal Length:**

0.375 inches

**Body Length:**

0.085 inches

**Body Outside Diameter:**

0.090 inches

**Terminal Diameter:**

0.00396 inches

**Maximum Power Dissipation Rating:**

5.00 milliwatts

**Ambient Temperature At Full Rated Power:**

125.0 degrees celsius

**Maximum Operating Temp:**

125.0 degrees celsius

**Thermal Time Constant In Seconds:**

3.0

**Power Dissipation Constant In Milliwatts Per Deg Celsius:**

0.5

**Zero Power Temperature Coefficient Of Resistance In Percent Per Deg Celsius:**

5.00

**Temperature Points For Resistance Readings At Zero Power:**

76.81 degrees celsius 5th resistance-temperature point

**Zero Power Resistance At Specificationified Temp:**

9.579 megohms 1st resistance-temperature point

**Resistance Tolerance At A Specificationified Temperature In Percent:**

-0.0/+5.0 7th resistance-temperature point

**Inclosure Type:**

Encapsulated

**Zero Power Resistance:**

100.000 kilohms

**Zero Power Resistance Tolerance In Percent At Reference Temp:**

-10.0/+10.0

**Special Features:**

Two beads welded together

**Precious Material And Location:**

Terminal surfaces iridium and terminal surfaces platinum

**Precious Material:**

Iridium and platinum

**Style Designator:**

Sealed or coated bead

**Test Data Document:**

06481-912128 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

2 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A086a0