NSN 5905-00-321-8010

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-321-8010

Section Quantity:				
1				
Body Style:				
Rectangular				
Reliability Indicator:				
Not established				
Body Length:				
0.280 inches				
Body Width:				
0.265 inches				
Body Height:				
0.165 inches				
Actuator Type:				
Flush drive with slot-hole				
Effective Electrical Rotation In Deg Angular Rotation:				
270.0				
Terminal Location:				
Dual inline				
Mounting Method:				
Terminal				
Electrical Resistance Per Section:				
2.0 kilohms single section				
Rotary Actuator Travel In Angular Deg:				
270.0				
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:				
125.0 single section				
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:				
-150.0 to 150.0 single section				
Power Dissipation Rating Per Section In Watts:				
0.5 free air single section				
Resistance Tolerance Per Section In Percent:				
-20.0 to 20.0 single section				
Actuator Travel Control Feature:				
Stops				
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:				
25.0 single section				
Standard Taper Curve Per Section:				
A single section				
Terminal Type And Quantity:				
4 tab, solder lug				
Shelf Life:				
N/a				

NSN 5905-00-321-8010

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



	nit	O+	Measure:
u		v	wicasuic.

--

Demilitarization:

No

Fiig:

A002a0