

View Online at <https://aerobasegroup.com/nsn/5905-00-324-4999>

Section Quantity:

3

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Overall Length:

2.687 inches

Terminal Length:

0.344 inches

Body Diameter:

Between 1.046 inches and 1.078 inches

Shaft Diameter:

Between 0.248 inches and 0.251 inches

Shaft Length:

Between 0.609 inches and 0.641 inches

Mounting Bushing Length:

0.375 inches

Body Length:

Between 1.796 inches and 1.828 inches

Overall Diameter:

1.406 inches

Shaft Style:

Round

Actuator Type:

Single shaft

Nonturn Device Location:

At 3 oclock and at 9 oclock

Nonturn Device Radius:

Between 0.515 inches and 0.547 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thread Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Locking bushing

Electrical Resistance Per Section:

200.000 kilohms 3rd section

Power Dissipation Rating Per Section In Watts:

2.0 free air single section

Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 1st section

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

120.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

9 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0