NSN 5905-00-326-1940

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-326-1940

Section Overther
Section Quantity:
Body Style:
Cylindrical
Reliability Indicator:
Not established
Overall Length:
0.765 inches
Body Diameter:
0.781 inches
Body Length:
0.391 inches
Overall Diameter:
0.781 inches
Actuator Type:
Flush drive with slot-hole
Maximum Starting Torque:
6.00 inch-ounces
Nonturn Device Location:
At 3 oclock and at 9 oclock
Nonturn Device Radius:
0.405 inches
Terminal Location:
Rear end
Mounting Method:
Tab
Electrical Resistance Per Section:
250.0 ohms single section
Rotary Actuator Travel In Angular Deg:
270.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
105.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Actuator Travel Control Feature:
Stops
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-150.0 to 150.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

55.0 single section

NSN 5905-00-326-1940

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Fiig: A002a0