NSN 5905-00-328-0108

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-328-0108

Continu Overstitus
Section Quantity:
Body Style:
Cylindrical
Reliability Indicator:
Not established
Overall Length:
0.906 inches
Terminal Length:
0.547 inches
Body Diameter:
0.500 inches
Body Length:
0.359 inches
Overall Diameter:
0.500 inches
Actuator Type:
Flush drive with slot-hole
Effective Electrical Rotation In Deg Angular Rotation:
295.0
Maximum Starting Torque:
3.00 inch-ounces
Maximum Running Torque:
0.25 inch-ounces
Maximum Stop Torque:
32.00 inch-ounces
Center To Center Distance Between Terminals:
0.200 inches
Terminal Location:
Rear end
Mounting Method:
Terminal
Electrical Resistance Per Section:
1.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
295.0
Center To Center Distance Between Center Terminal And Outside Terminal:
0.100 inches
Resistance Tempurature Characteristic Range Per Section In Percent:
+0.0 to 5.5 -55 degrees celsius single section and +0.0 to 3.0 -25 degrees celsius single section and +0.0 to 1.5 0 degrees celsius single
section and -0.0 to 0.0 25 degrees celsius single section and -2.0 to 2.0 85 degrees celsius single section and +0.0 to 4.5 120 degrees

120.0 single section

celsius single section

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

NSN 5905-00-328-0108

A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Power Dissipation Rating Per Section In Watts:
0.25 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: