Precision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-328-1696

Section Quantity:

1

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

1.8750 inches

Pilot Length:

0.0600 inches

Overall Length:

1.831 inches

Undercut Diameter:

1.875 inches

Undercut Width:

0.0600 inches

Body Diameter:

2.000 inches

Shaft Diameter:

0.250 inches

Shaft Length:

0.810 inches

Body Length:

0.985 inches

Overall Diameter:

2.312 inches

Mounting Lip Diameter:

2.0000 inches

Mounting Lip Depth:

0.0600 inches

Shaft Style:

Round

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

360.0

Maximum Starting Torque:

0.60 inch-ounces

Shaft Runout:

0.001 inches

Lateral Runout:

0.002 inches

NSN 5905-00-328-1696

Precision Nonwire Wound Variable Resistor - Page 2 of 2



Pilot Diameter Run	Dut:
0.001 inches	
Terminal Location:	
Radially positioned	ver more than half the circumference
Mounting Method:	
Clamp ring	
Electrical Resistan	ce Per Section:
5.0 kilohms single s	ction
Rotary Actuator Tr	ivel In Angular Deg:
360.0	
Function Conform	y Tolerance Per Section:
-0.15/+0.15 single s	ction
Ambient Tempurat	re In Deg Celsius Per Section At Zero Percent Rated Power:
160.0 single section	
Tempurature Coeff	cient Of Resistance Per Section In Ppm Per Deg Celsius:
-400.0/+400.0 single	section
Power Dissipation	Rating Per Section In Watts:
4.0 free air single se	ction
Function Conformi	y Per Section:
Single section absol	ute linearity
Resistance Tolerar	ce Per Section In Percent:
-10.0/+10.0 single s	ction
Actuator Travel Co	ntrol Feature:
Continuous motion	
Function Characte	istic Per Section:
Single section 360 c	egrees sine-cosine
Ambient Tempurat	ire In Deg Celsius Per Section At Full Rated Power:
85.0 single section	
Test Data Docume	t:
64402-98659 drawir	g (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
excludes any specif	cation, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And	Quantity:
4 turret	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A002a0	