Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-328-1761

Section Quantity:

1

Body Style:

Rectangular

Reliability Indicator:

Not established

Terminal Length:

0.188 inches

Shaft Diameter:

0.070 inches

Shaft Length:

0.040 inches

Body Length:

0.250 inches

Body Width:

0.185 inches

Body Height:

0.250 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

4320.0

Center To Center Distance Between Terminals:

0.200 inches

Terminal Location:

Left adjacent side single row

Mounting Method:

Terminal

Electrical Resistance Per Section:

20.0 ohms single section

Rotary Actuator Travel In Angular Deg:

4320.0

Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

175.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0 to 100.0 single section

Power Dissipation Rating Per Section In Watts:

0.25 free air single section



Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 single section

Actuator Travel Control Feature:

Clutch

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0