Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-328-2178

Section	Quantity:	

1

Body Style:

Rectangular

**Reliability Indicator:** 

Not established

**Terminal Length:** 

0.200 inches

**Body Length:** 

0.240 inches

**Body Width:** 

0.390 inches

Body Height:

0.360 inches

Actuator Type:

#### Flush drive with slot-hole

Effective Electrical Rotation In Deg Angular Rotation:

280.0

**Center To Center Distance Between Terminals:** 

0.200 inches

**Terminal Location:** 

Rear end

### **Mounting Method:**

Terminal

**Electrical Resistance Per Section:** 

100.0 ohms single section

**Rotary Actuator Travel In Angular Deg:** 

310.0

Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

### Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-150.0 to 150.0 single section

#### **Power Dissipation Rating Per Section In Watts:**

0.5 free air single section

# **Resistance Tolerance Per Section In Percent:**

-20.0 to 20.0 single section

# **Actuator Travel Control Feature:**

Stops

### Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section



Standard Taper Curve Per Section:

A single section

# Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0