

View Online at <https://aerobasegroup.com/nsn/5905-00-331-7101>

Section Quantity:

1

Body Style:

Cylindrical

Reliability Indicator:

Not established

Terminal Length:

Between 0.158 inches and 0.218 inches

Body Diameter:

Between 0.329 inches and 0.359 inches

Body Length:

Between 0.329 inches and 0.359 inches

Shaft Bearing Type:

Sleeve

Actuator Type:

Flush drive with slot-hole

Effective Electrical Rotation In Deg Angular Rotation:

240.0

Maximum Starting Torque:

5.00 inch-ounces

Maximum Running Torque:

5.00 inch-ounces

Maximum Stop Torque:

10.00 inch-ounces

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

0.100 inches

Center To Center Distance Between Terminals:

Between 0.190 inches and 0.210 inches

Fragility Factor:

Moderately rugged

Terminal Location:

Lower adjacent side two rows

Mounting Method:

Terminal

Center To Center Distance Between Terminal Rows:

Between 0.090 inches and 0.110 inches

Features Provided:

Humidity proof

Cubic Measure:

0.038 cubic inches

Electrical Resistance Per Section:

1.0 megohms single section

Rotary Actuator Travel In Angular Deg:

280.0

Center To Center Distance Between Center Terminal And Outside Terminal:

Between 0.090 inches and 0.110 inches

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0 to 100.0 single section

Power Dissipation Rating Per Section In Watts:

0.5 free air single section

Resistance Tolerance Per Section In Percent:

-20.0 to 20.0 single section

Actuator Travel Control Feature:

Stops

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0