## NSN 5905-00-332-9671

No

Noninductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-332-9671

| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:   |
|---|
| -10.0/+10.0   |
| Electrical Resistance:  |
| 2.500 kilohms   |
| Resistance Tolerance In Percent:  |
| -0.020/+0.020   |
| Ambient Tempurature In Deg Celsius At Full Rated Power:   |
| 70.0  |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:   |
| 145.0   |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius:  |
| +0.0/+125.0   |
| Inclosure Method:   |
| Encapsulated  |
| Terminal Type:  |
| Wire lead   |
| Reliability Indicator:  |
| Established   |
| Reliability Failure Rate Level In Percent:  |
| 0.010   |
| Terminal Length:  |
| 1.500 inches  |
| Body Diameter:  |
| Between 0.219 inches and 0.281 inches   |
| Body Length:  |
| Between 0.688 inches and 0.812 inches   |
| Power Dissipation Rating In Watts:  |
| 0.250 free air  |
| Cubic Measure (non-core):   |
| 0.050 cubic inches  |
| Unpackaged Unit Weight:   |
| 2.5 grams   |
| Style Designator:   |
| Axial terminal each end   |
| Test Data Document:   |
| 18338-108219 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; |
| excludes any specification, standard or other document that may be referenced in a basic governing drawing)                             |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |

## NSN 5905-00-332-9671

Noninductive Wire Wound Fixed Resistor - Page 2 of 2



Fiig:

A001a0