## NSN 5905-00-333-8798

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-333-8798 **Section Quantity: Body Style:** Cylindrical w/readout **Reliability Indicator:** Not established **Pilot Diameter:** 0.4040 inches **Body Diameter:** 0.750 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 1.000 inches **Actuator Type:** Integral knob with counter **Effective Electrical Rotation In Deg Angular Rotation:** 3600.0 **Nonturn Device Location:** At 9 oclock **Nonturn Device Radius:** 0.280 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over more than half the circumference **Mounting Method:** Standard bushing **Features Provided:** Hermetically sealed **Electrical Resistance Per Section:** 1.0 kilohms single section **Rotary Actuator Travel In Angular Deg:** 3600.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 85.0 single section

**Power Dissipation Rating Per Section In Watts:** 

1.5 free air single section

## NSN 5905-00-333-8798

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Resistance Tolerance Per Section In Percent:
-5.0 to 5.0 single section
Actuator Travel Control Feature:
Clutch
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-20.0 to 20.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
25.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 wire loop
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No