

View Online at <https://aerobasegroup.com/nsn/5905-00-337-6279>

Section Quantity:

1

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

0.7500 inches

Pilot Length:

0.0620 inches

Undercut Diameter:

0.781 inches

Undercut Width:

0.0620 inches

Body Diameter:

0.750 inches

Shaft Diameter:

0.125 inches

Shaft Length:

0.500 inches

Body Length:

0.747 inches

Mounting Lip Diameter:

0.8750 inches

Mounting Lip Depth:

0.0620 inches

Shaft Style:

Round

Actuator Type:

Double ended shaft

Effective Electrical Rotation In Deg Angular Rotation:

345.0

Maximum Starting Torque:

0.10 inch-ounces

Maximum Running Torque:

0.10 inch-ounces

Shaft End Play:

0.00500 inches

Shaft Runout:

0.001 inches

Lateral Runout:

0.002 inches

Pilot Diameter Runout:

0.0015 inches

Shaft Radial Play:

0.002 inches

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Clamp ring

Electrical Resistance Per Section:

20.0 kilohms single section

Rotary Actuator Travel In Angular Deg:

360.0

Function Conformity Tolerance Per Section:

-0.50/+0.50 single section

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-250.0/+250.0 single section

Power Dissipation Rating Per Section In Watts:

1.2 free air single section

Function Conformity Per Section:

Single section independent linearity

Resistance Tolerance Per Section In Percent:

-5.0/+5.0 single section

Actuator Travel Control Feature:

Continuous motion

Function Characteristic Per Section:

Single section linear

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

60.0 single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0