## NSN 5905-00-337-7515

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-337-7515 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 1.495 inches **Body Diameter:** 1.220 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.875 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 0.620 inches **Overall Diameter:** 1.750 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** Between 290.0 and 305.0 **Maximum Starting Torque:** 6.00 inch-ounces **Maximum Running Torque:** 1.20 inch-ounces **Maximum Stop Torque:** 128.00 inch-ounces **Nonturn Device Location:** At 9 oclock **Nonturn Device Radius: Screw Thread Series Designator:** 

0.531 inches **Screw Thread Diameter:** 0.375 inches Unef Screw Thready Qty Per Inch (tpi): 32.0

## NSN 5905-00-337-7515

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Torminal Lagation.	
Terminal Location:	
Radially positioned over less than half the circumference	
Mounting Method:	
Standard bushing	
Features Provided:	
Panel seal	
Electrical Resistance Per Section:	
200.0 ohms single section	
Rotary Actuator Travel In Angular Deg:	
Between 290.0 and 305.0	
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:	
105.0 single section	
Power Dissipation Rating Per Section In Watts:	
2.0 free air single section	
Resistance Tolerance Per Section In Percent:	
-10.0 to 10.0 single section	
Actuator Travel Control Feature:	
Stops	
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:	
40.0 single section	
Standard Taper Curve Per Section:	
A single section	
Test Data Document:	
81349-mil-r-19 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formations.	at
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental	
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	
Terminal Type And Quantity:	
3 tab, solder lug	
Specification Data:	
81349-mil-r-19/2 government specification	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A002a0	