## NSN 5905-00-340-2738

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-340-2738 **Section Quantity: Body Style:** Cylindrical hole/slot mounted **Reliability Indicator:** Not established **Body Diameter:** 1.750 inches **Mounting Hole Diameter:** 0.088 inches **Shaft Diameter:** 0.250 inches Shaft Length: 0.375 inches **Body Length:** 1.960 inches **Mounting Hole/stud Circle Diameter:** 0.874 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation: Mounting Facility Quantity:** 2 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Clamp ring and unthreaded hole **Electrical Resistance Per Section:** 10.0 kilohms 3rd section **Rotary Actuator Travel In Angular Deg:** 240.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 120.0 all sections **Power Dissipation Rating Per Section In Watts:** 0.5 free air all sections **Resistance Tolerance Per Section In Percent:** -5.0 to 5.0 all sections

Actuator Travel Cont

**Actuator Travel Control Feature:** 

Stops

## NSN 5905-00-340-2738

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:	
70.0 all sections	
Standard Taper Curve Per Section:	
A all sections	
Terminal Type And Quantity:	
9 turret	
Shelf Life:	
N/a	
Unit Of Measure:	
<del></del>	
Demilitarization:	
No	