## NSN 5905-00-340-9423

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-340-9423

Section Quantity:
Body Style:
Cylindrical bushing mounted
Overall Length:
2.810 inches
Shaft Diameter:
0.2497 inches
Mounting Bushing Length:
0.310 inches
Body Length:
2.000 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Nonturn Device Location:
At 12 oclock
Shaft End Play:
0.00500 inches
Lateral Runout:
0.003 inches
Pilot Diameter Runout:
0.00200 inches
Shaft Radial Play:
0.003 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
1.000 kilohms single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
85.0 single section
Power Dissipation Rating Per Section In Watts:
5.0 free air single section
Resistance Tolerance Per Section In Percent:

-3.0/+3.0 single section

## NSN 5905-00-340-9423

Precision Wire Wound Variable Resistor - Page 2 of 2



-20.0/+20.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

**Terminal Type And Quantity:** 

3 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A002a0