

View Online at <https://aerobasegroup.com/nsn/5905-00-345-0688>

**Section Quantity:**

1

**Body Style:**

Cylindrical hole/slot mounted

**Reliability Indicator:**

Not established

**Overall Length:**

0.582 inches

**Body Diameter:**

0.625 inches

**Mounting Hole Diameter:**

0.083 inches

**Shaft Diameter:**

Between 0.155 inches and 0.156 inches

**Shaft Length:**

0.535 inches

**Body Length:**

0.186 inches

**Overall Diameter:**

0.625 inches

**Mounting Hole/stud Circle Diameter:**

0.427 inches

**Shaft Style:**

Round, slotted

**Actuator Type:**

Double ended shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

260.0

**Fragility Factor:**

Moderately rugged

**Mounting Facility Quantity:**

2

**Terminal Location:**

Front end

**Mounting Method:**

Unthreaded hole

**Features Provided:**

Humidity proof

**Cubic Measure:**

0.068 cubic inches

**Electrical Resistance Per Section:**

5.0 kilohms single section

**Rotary Actuator Travel In Angular Deg:**

260.0

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

125.0 single section

**Power Dissipation Rating Per Section In Watts:**

0.1 free air single section

**Resistance Tolerance Per Section In Percent:**

-20.0 to 20.0 single section

**Actuator Travel Control Feature:**

Stops

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

25.0 single section

**Standard Taper Curve Per Section:**

A single section

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0