## NSN 5905-00-346-7948

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-346-7948

Electrical Resistance:  16.200 kilohms  Resistance Tolerance In Percent:  1.000/+1.000  Ambient Tempurature In Deg Celsius At Full Rated Power:  125.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  175.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0/+175.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Established  Reliability Failure Rate Level In Percent:  0.005 inches  Body Diameter:  0.065 inches  Body Length:  0.150 inches
Resistance Tolerance In Percent:  1.1.000/+1.000  Ambient Tempurature In Deg Celsius At Full Rated Power:  125.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  175.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  155.0/+175.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Established  Reliability Failure Rate Level In Percent:  0.001  Body Diameter:  0.065 inches  Body Length:
Resistance Tolerance In Percent:  1.1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power:  125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius:  155.0/+175.0 Inclosure Method: Encapsulated Terminal Type:  Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent:  0.0001 Body Diameter:  0.065 inches Body Length:
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.065 inches Body Length:
Ambient Tempurature In Deg Celsius At Full Rated Power:  125.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  175.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  155.0/+175.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Established  Reliability Failure Rate Level In Percent:  10.001  Body Diameter:  10.005 inches  Body Length:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  175.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  155.0/+175.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Established  Reliability Failure Rate Level In Percent:  10.001  Body Diameter:  10.005 inches  Body Length:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  175.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  155.0/+175.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Established  Reliability Failure Rate Level In Percent:  0.001  Body Diameter:  0.065 inches  Body Length:
Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Fempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0/+175.0  Inclosure Method:  Encapsulated  Ferminal Type:  Wire lead  Reliability Indicator:  Established  Reliability Failure Rate Level In Percent:  0.001  Body Diameter:  0.065 inches  Body Length:
nclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.065 inches Body Length:
Encapsulated Ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.065 inches Body Length:
Encapsulated  Ferminal Type:  Wire lead  Reliability Indicator:  Established  Reliability Failure Rate Level In Percent:  0.001  Body Diameter:  0.065 inches  Body Length:
Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.065 inches Body Length:
Wire lead  Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001  Body Diameter: 0.065 inches  Body Length:
Reliability Indicator:  Established  Reliability Failure Rate Level In Percent:  0.001  Body Diameter:  0.065 inches  Body Length:
Established  Reliability Failure Rate Level In Percent:  0.001  Body Diameter:  0.065 inches  Body Length:
Reliability Failure Rate Level In Percent:  0.001  Body Diameter:  0.065 inches  Body Length:
D.001  Body Diameter: D.065 inches  Body Length:
Body Diameter:  0.065 inches  Body Length:
D.065 inches  Body Length:
Body Length:
).150 inches
Power Dissipation Rating In Watts:
0.050 free air
Style Designator:
Axial terminal each end
Test Data Document:
31349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig:
A001a0