

View Online at <https://aerobasegroup.com/nsn/5905-00-347-1334>

Section Quantity:

3

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

0.8750 inches

Pilot Length:

0.0930 inches

Undercut Diameter:

1.875 inches

Undercut Width:

0.0730 inches

Body Diameter:

2.000 inches

Shaft Diameter:

0.249 inches

Shaft Length:

0.500 inches

Body Length:

2.781 inches

Mounting Lip Diameter:

1.8750 inches

Mounting Lip Depth:

0.0620 inches

Shaft Style:

Round

Shaft Bearing Type:

Sleeve

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

320.0

Maximum Starting Torque:

0.80 inch-ounces

Maximum Stop Torque:

3.00 inch-ounces

Nonturn Device Location:

At 3 oclock

Nonturn Device Radius:

1.281 inches

Shaft End Play:

0.0045 inches

Shaft Runout:

0.002 inches

Lateral Runout:

0.002 inches

Pilot Diameter Runout:

0.0015 inches

Shaft Radial Play:

0.002 inches

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Clamp ring

Electrical Resistance Per Section:

2.0 percent, rated amperes c and better select

Rotary Actuator Travel In Angular Deg:

320.0

Function Conformity Tolerance Per Section:

-0.04/+0.04 all sections

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 all sections

Power Dissipation Rating Per Section In Watts:

6.0 free air all sections

Function Conformity Per Section:

All sections independent linearity

Resistance Tolerance Per Section In Percent:

-1.5/+1.5 1st section

Actuator Travel Control Feature:

Continuous motion

Function Characteristic Per Section:

All sections linear

Temperature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:

-20.0/+20.0 all sections

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

25.0 all sections

Terminal Type And Quantity:

9 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0