## NSN 5905-00-347-1338

**Section Quantity:** 

**Body Style:** 

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-347-1338

Cylindrical bushing mounted
Reliability Indicator:
Not established
Overall Length:
2.250 inches
First Flat Length:
0.344 inches
Flat Height:
0.090 inches
Body Diameter:
2.312 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.875 inches
Mounting Bushing Length:
0.375 inches
Body Length:
1.375 inches
Shaft Style:
Round, flatted
Actuator Type:
Single shaft
<b>Nonturn Device Location:</b>
At 6 oclock
Nonturn Device Radius:
0.531 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Mounting Facility Quantity:
2
Terminal Location:
Lower adjacent side single row
Mounting Method:
Standard bushing

## NSN 5905-00-347-1338

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:
200.000 ohms single section
Power Dissipation Rating Per Section In Watts:
50.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Standard Taper Curve Per Section:
X single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A002a0