NSN 5905-00-350-1562

Noninductive Wire Wound Fixed Resistor - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5905-00-350-1562 |
|--|
| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: |
| -10.0/+10.0 |
| Electrical Resistance: |
| 1.000 kilohms |
| Resistance Tolerance In Percent: |
| -0.050/+0.050 |
| Ambient Tempurature In Deg Celsius At Full Rated Power: |
| 125.0 |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: |
| 145.0 |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius: |
| -65.0/+145.0 |
| Inclosure Method: |
| Encapsulated |
| Terminal Type: |
| Wire lead |
| Reliability Indicator: |
| Established |
| Reliability Failure Rate Level In Percent: |
| 0.010 |
| Terminal Length: |
| 1.500 inches |
| Body Diameter: |
| Between 0.235 inches and 0.265 inches |
| Body Length: |
| Between 0.312 inches and 0.364 inches |
| Power Dissipation Rating In Watts: |
| 0.125 free air |
| Cubic Measure (non-core): |
| 0.017 cubic inches |
| Unpackaged Unit Weight: |
| 1.5 grams |
| Style Designator: |
| Axial terminal each end |
| Test Data Document: |
| 81349-mil-r-39005 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Specification Data: |
| 81349-mil-r-39005/5 government specification |
| Shelf Life: |

-

N/a

Unit Of Measure:

NSN 5905-00-350-1562

Noninductive Wire Wound Fixed Resistor - Page 2 of 2



| _ | | •• | • • | | | | |
|----|----|----|-----|-----|-----|---|----|
| וו | em | ш | 112 | rız | 211 | n | ٠. |
| | | | | | | | |

No

Fiig:

A001a0