

View Online at <https://aerobasegroup.com/nsn/5905-00-350-1696>

**Section Quantity:**

1

**Body Style:**

Cylindrical servo mounted

**Reliability Indicator:**

Not established

**Pilot Diameter:**

0.6250 inches

**Pilot Length:**

0.0620 inches

**Overall Length:**

2.107 inches

**Undercut Diameter:**

0.781 inches

**Undercut Width:**

0.0620 inches

**Body Diameter:**

0.880 inches

**Shaft Diameter:**

0.1248 inches

**Shaft Length:**

0.500 inches

**Body Length:**

1.576 inches

**Overall Diameter:**

1.135 inches

**Mounting Lip Diameter:**

0.8750 inches

**Mounting Lip Depth:**

0.0620 inches

**Shaft Style:**

Round

**Shaft Bearing Type:**

Ball

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

3600.0

**Maximum Starting Torque:**

0.60 inch-ounces

**Maximum Running Torque:**

0.50 inch-ounces

**Maximum Stop Torque:**

100.00 inch-ounces

**Shaft End Play:**

0.002 inches

**Shaft Runout:**

0.001 inches

**Lateral Runout:**

0.002 inches

**Pilot Diameter Runout:**

0.0015 inches

**Shaft Radial Play:**

0.001 inches

**Terminal Location:**

Longitudinally positioned on the circumference

**Mounting Method:**

Clamp ring

**Electrical Resistance Per Section:**

10.0 kilohms single section

**Rotary Actuator Travel In Angular Deg:**

3600.0

**Function Conformity Tolerance Per Section:**

-0.10/+0.10 single section

**Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:**

-70.0/+70.0 single section

**Power Dissipation Rating Per Section In Watts:**

2.0 free air single section

**Function Conformity Per Section:**

Single section independent linearity

**Fixed Tap Quantity Per Section:**

1 single section

**Tap Location Tolerance Per Section:**

-2.5/+2.5 ohms 1st section

**Resistance Tolerance Per Section In Percent:**

-5.0/+5.0 single section

**Actuator Travel Control Feature:**

Stops

**Criticality Code Justification:**

Crgd

**Function Characteristic Per Section:**

Single section linear

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

63.0 single section

**Test Data Document:**

18876-10243517 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

4 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0