## NSN 5905-00-351-6765

Noninductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-351-6765

| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:  |
|--|
| -90.0/+90.0  |
| Electrical Resistance:   |
| 0.100 ohms   |
| Resistance Tolerance In Percent:   |
| -1.000/+1.000  |
| Ambient Tempurature In Deg Celsius At Full Rated Power:  |
| 125.0  |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  |
| 145.0  |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius:   |
| -65.0/+145.0   |
| Inclosure Method:  |
| Encapsulated   |
| Terminal Type:   |
| Wire lead  |
| Reliability Indicator:   |
| Established  |
| Reliability Failure Rate Level In Percent:   |
| 0.001  |
| Terminal Length:   |
| 1.500 inches   |
| Body Diameter:   |
| 0.250 inches   |
| Body Length:   |
| 0.500 inches   |
| Power Dissipation Rating In Watts:   |
| 0.150 free air   |
| Cubic Measure (non-core):  |
| 0.024 cubic inches   |
| Unpackaged Unit Weight:  |
| 2.0 grams  |
| Style Designator:  |
| Axial terminal each end  |
| Test Data Document:  |
| 81349-mil-r-39005 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain          |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).                            |
| Specification Data:  |
| 81349-mil-r-39005/4 government specification   |
| Shelf Life:  |
| N/a  |

--

**Unit Of Measure:** 

## NSN 5905-00-351-6765

Noninductive Wire Wound Fixed Resistor - Page 2 of 2



| _  |    | •• | • • |     |     |   |    |
|----|----|----|-----|-----|-----|---|----|
| וו | em | ш  | 112 | rız | 211 | n | ٠. |
|    |    |    |     |     |     |   |    |

No

Fiig:

A001a0