NSN 5905-00-356-7951

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-356-7951

0. 0. 0. 0.
Section Quantity:
1
Body Style:
Cylindrical servo mounted
Reliability Indicator:
Not established
Pilot Diameter:
1.8750 inches
Pilot Length:
0.0620 inches
Overall Length:
1.750 inches
Undercut Diameter:
1.875 inches
Undercut Width:
0.0730 inches
Body Diameter:
2.000 inches
Shaft Diameter:
0.2497 inches
Shaft Length:
1.125 inches
Body Length:
0.625 inches
Overall Diameter:
2.210 inches
Mounting Lip Diameter:
2.0000 inches
Mounting Lip Depth:
0.0930 inches
Shaft Style:
Round
Shaft Bearing Type:
Ball
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
350.0
Maximum Starting Torque:
1.00 inch-ounces
Maximum Punning Torque

0.60 inch-ounces

NSN 5905-00-356-7951

Precision Wire Wound Variable Resistor - Page 2 of 3



Chaff End Dlave
Shaft End Play:
0.003 inches
Shaft Runout:
0.001 inches
Lateral Runout:
0.003 inches
Pilot Diameter Runout:
0.002 inches
Shaft Radial Play:
0.0015 inches
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring
Electrical Resistance Per Section:
50.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-0.30/+0.30 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Power Dissipation Rating Per Section In Watts:
4.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-3.0/+3.0 single section
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
Single section linear
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-20.0/+20.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Test Data Document:
80070-17-13339 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
3 turret
Shelf Life:
N/a
Unit Of Measure:

NSN 5905-00-356-7951

Precision Wire Wound Variable Resistor - Page 3 of 3



Demilitarization:

No

Fiig:

A002a0