## NSN 5905-00-359-2946

**Section Quantity:** 

Cylindrical bushing mounted

**Body Style:** 

Overall Length: 2.937 inches

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-359-2946

Body Diameter:
1.812 inches
Shaft Diameter:
0.250 inches
Mounting Bushing Length:
0.312 inches
Overall Diameter:
2.063 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Nonturn Device Location:
At 12 oclock
Shaft End Play:
0.00500 inches
Lateral Runout:
0.003 inches
Pilot Diameter Runout:
0.00200 inches
Shaft Radial Play:
0.003 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Mounting Method:
Standard bushing
Features Provided:
Nonmetallic shaft
Electrical Resistance Per Section:
20.000 kilohms single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section

## NSN 5905-00-359-2946

Precision Wire Wound Variable Resistor - Page 2 of 2



## **Power Dissipation Rating Per Section In Watts:**

5.0 free air single section

**Resistance Tolerance Per Section In Percent:** 

-3.0/+3.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

**Terminal Type And Quantity:** 

3 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A002a0