NSN 5905-00-359-6189

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-359-6189

Section Quantity:
1
Body Style:
Rectangular w/bushing/holes/slots
Reliability Indicator:
Not established
Overall Length:
1.562 inches
Overall Height:
0.508 inches
Overall Width:
0.257 inches
Mounting Hole Diameter:
0.093 inches
Shaft Diameter:
0.275 inches
Shaft Length:
0.250 inches
Mounting Bushing Length:
0.250 inches
Body Length:
1.250 inches
Body Width:
0.257 inches
Body Height:
0.320 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
7920.0
Lateral Distance Between Mounting Hole Centers:
1.000 inches
Screw Thread Diameter:
0.216 inches
Screw Thread Series Designator:
Unf
Screw Thready Qty Per Inch (tpi):
28.0
Mounting Facility Quantity:

NSN 5905-00-359-6189

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Terminal Location:
Lower adjacent side two rows
Mounting Method:
Standard bushing w/panel seal and unthreaded hole
Features Provided:
Humidity proof
Electrical Resistance Per Section:
50.0 ohms single section
Rotary Actuator Travel In Angular Deg:
7920.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-100.0 to 100.0 single section
Power Dissipation Rating Per Section In Watts:
0.8 free air single section
Resistance Tolerance Per Section In Percent:
-20.0 to 20.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 wire loop
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0