Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-359-7765

# Section Quantity:

1

Body Style:

Cylindrical bushing mounted

# **Reliability Indicator:**

Not established

## **Overall Length:**

2.452 inches

### Body Diameter:

1.156 inches

Shaft Diameter:

0.250 inches

Shaft Length:

1.218 inches

### Mounting Bushing Length:

# 0.375 inches

**Body Length:** 

0.828 inches

## **Overall Diameter:**

1.518 inches

### Shaft Style:

Round

### Switch Type:

Rotary

# Switch Voltage Rating In Volts:

117.0

### Actuator Type:

Single shaft

### Maximum Starting Torque:

6.00 inch-ounces

### Maximum Running Torque:

1.00 inch-ounces

### Maximum Stop Torque:

128.00 inch-ounces

### Nonturn Device Location:

At 9 oclock

# Nonturn Device Radius:

0.531 inches

## Switch Operating Position:

Start of rotation

### Switch Contact Arrangement:

Single pole, single throw, normally open, both positions maintained



Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

**Terminal Location:** 

Rear-bottom

## Mounting Method:

Standard bushing

**Features Provided:** 

Switch

Electrical Resistance Per Section:

2.5 kilohms single section

**Rotary Actuator Travel In Angular Deg:** 

335.0

## Resistance Tempurature Characteristic Range Per Section In Percent:

-3.0 to 0.0 -55 degrees celsius single section and -5.0 to 10.0 -25 degrees celsius single section and -5.0 to 10.0 25 degrees celsius single

section and -0.0 to 3.0 120 degrees celsius single section

## Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 single section

# Power Dissipation Rating Per Section In Watts:

2.0 free air single section

# **Resistance Tolerance Per Section In Percent:**

-10.0 to 10.0 single section

# Actuator Travel Control Feature:

Stops

# Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Switch Current Type And Rating In Amps:

3.000 ac

# Standard Taper Curve Per Section:

A single section

### **Terminal Type And Quantity:**

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

## Demilitarization:

No

Fiig:

A002a0