NSN 5905-00-361-8860

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-361-8860 **Section Quantity:** 2 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 0.9688 inches Pilot Length: 0.0620 inches **Overall Length:** 1.634 inches **Undercut Diameter:** 0.968 inches **Undercut Width:** 0.0620 inches **Body Diameter:** 1.062 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.310 inches **Body Length:** 1.160 inches **Overall Diameter:** 1.449 inches **Mounting Lip Diameter:** 1.0620 inches **Mounting Lip Depth:** 0.0620 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Terminal Location:** Longitudinally positioned on the circumference **Mounting Method:** Clamp ring **Features Provided:** Nonmetallic shaft

Electrical Resistance Per Section: 50.0 kilohms all sections

NSN 5905-00-361-8860

No Fiig: A002a0

Precision Wire Wound Variable Resistor - Page 2 of 2



Function Conformity Tolerance Per Section: -0.50/+0.50 single section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 80.0 single section **Power Dissipation Rating Per Section In Watts:** 2.0 free air single section **Function Conformity Per Section:** Single section independent linearity **Resistance Tolerance Per Section In Percent:** -5.0/+5.0 all sections **Function Characteristic Per Section:** Single section linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 25.0 single section **Terminal Type And Quantity:** 4 turret Shelf Life: N/a **Unit Of Measure: Demilitarization:**