## NSN 5905-00-362-5058

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-362-5058 **Section Quantity:** 1 **Body Style:** Rectangular w/mounting holes/slots **Reliability Indicator:** Not established **Overall Length:** 0.530 inches **Terminal Length:** Between 0.500 inches and 0.530 inches **Overall Height:** 1.000 inches **Overall Width:** 0.220 inches **Mounting Hole Diameter:** 0.078 inches **Shaft Diameter:** 0.030 inches **Shaft Length:** 0.080 inches **Body Length:** 0.520 inches **Body Width:** 0.500 inches **Body Height:** 0.220 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Maximum Starting Torque:** 5.00 inch-ounces **Center To Center Distance Between Terminals:** 0.200 inches **Lateral Distance Between Mounting Hole Centers:** 0.500 inches **Mounting Facility Quantity:** 2

**Terminal Location:** 

Lower adjacent side two rows

**Mounting Method:** 

Terminal and unthreaded hole

## NSN 5905-00-362-5058

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



| Center To Center Distance Between Terminal Rows:                            |
|---|
| 0.100 inches  |
| Features Provided:  |
| Nonmetallic shaft   |
| Electrical Resistance Per Section:  |
| 200.0 ohms single section   |
| Rotary Actuator Travel In Angular Deg:                                      |
| 9000.0  |
| Center To Center Distance Between Center Terminal And Outside Terminal:     |
| 0.100 inches  |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: |
| 150.0 single section  |
| Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:   |
| 100.0 to 100.0 single section   |
| Power Dissipation Rating Per Section In Watts:                              |
| 1.0 free air single section   |
| Resistance Tolerance Per Section In Percent:                                |
| 10.0 to 10.0 single section   |
| Actuator Travel Control Feature:  |
| Clutch  |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:         |
| 70.0 single section   |
| Standard Taper Curve Per Section:   |
| A single section  |
| Terminal Type And Quantity:   |
| 3 pin   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
| <del>-</del>  |
| Demilitarization:   |
| No  |
| Filg:   |
| A002a0  |
|   |
|   |