NSN 5905-00-365-8658

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-365-8658

0.4.0.0.44
Section Quantity:
1 Posts Curlos
Body Style:
Rectangular w/mounting holes
Reliability Indicator:
Not established
Overall Length:
0.535 inches
Terminal Length:
0.500 inches
Overall Height:
0.990 inches
Overall Width:
0.220 inches
Mounting Hole Diameter:
0.078 inches
Shaft Diameter:
0.075 inches
Shaft Length:
0.035 inches
Body Length:
0.500 inches
Body Width:
0.220 inches
Body Height:
0.500 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Center To Center Distance Between Terminals:
0.200 inches
Lateral Distance Between Mounting Hole Centers:
0.520 inches
Mounting Facility Quantity:
2
Terminal Location:
Lower adjacent side single row
Mounting Method:
Terminal and unthreaded hole
Electrical Resistance Per Section:
25.0 kilohms single section

NSN 5905-00-365-8658

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



C	Center	То	Center	Distance	Between	Center	Termir	nal Ar	nd Ou	tside	Termiı	nal:

0.100 inches

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0 to 100.0 single section

Power Dissipation Rating Per Section In Watts:

1.0 free air single section

Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0