## NSN 5905-00-368-2572

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-368-2572

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Overall Length:
1.469 inches
Body Diameter:
0.500 inches
Shaft Diameter:
0.125 inches
Shaft Length:
0.625 inches
Mounting Bushing Length:
0.250 inches
Body Length:
0.594 inches
Overall Diameter:
0.938 inches
Shaft Style:
Round
Switch Type:
Rotary
Switch Voltage Rating In Volts:
125.0 and 28.0
Contact Arm Electrical Off Position:
Fully ccw
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
275.0
Maximum Starting Torque:
8.00 inch-ounces
Maximum Running Torque:
0.50 inch-ounces
Maximum Stop Torque:
64.00 inch-ounces
Nonturn Device Location:
At 9 oclock
Nonturn Device Radius:

0.245 inches

## NSN 5905-00-368-2572

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 3



Mechanical Backlash In Deg Angular Rotation:
3.0
Switch Operating Position:
Start of rotation
Switch Contact Arrangement:
Single pole, single throw, normally open, both positions maintained
Screw Thread Diameter:
0.250 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Rear-bottom
Mounting Method:
Standard bushing w/shaft seal
Features Provided:
Switch
Electrical Resistance Per Section:
5.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
295.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
120.0 single section
Power Dissipation Rating Per Section In Watts:
0.5 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Switch Current Type And Rating In Amps:
0.500 ac and 1.500 dc
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
5 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:

No

## NSN 5905-00-368-2572

Nonprecision Nonwire Wound Variable Resistor - Page 3 of 3



Fiig:

A002a0