## NSN 5905-00-368-8977

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-368-8977

| Ocation Oceantity   |
|---|
| Section Quantity:   |
|   |
| Body Style:   |
| Cylindrical bushing mounted   |
| Reliability Indicator:  |
| Not established   |
| Overall Length:   |
| 25.000 millimeters  |
| Body Diameter:  |
| 20.000 millimeters  |
| Shaft Diameter:   |
| 6.000 millimeters   |
| Shaft Length:   |
| 15.000 millimeters  |
| Body Length:  |
| 10.000 millimeters  |
| Overall Diameter:   |
| 25.800 millimeters  |
| Shaft Style:  |
| Round, slotted  |
| Actuator Type:  |
| Single shaft  |
| Nonturn Device Location:  |
| At 9 oclock   |
| Nonturn Device Radius:  |
| 7.500 millimeters   |
| Terminal Location:  |
| Radially positioned over less than half the circumference           |
| Mounting Method:  |
| Locking bushing   |
| Features Provided:  |
| Nonmetallic shaft   |
| Electrical Resistance Per Section:                                  |
| 10.0 kilohms single section   |
| Power Dissipation Rating Per Section In Watts:                      |
| 0.25 free air single section  |
| Resistance Tolerance Per Section In Percent:                        |
| -10.0 to 10.0 single section  |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: |
| 50.0 single section   |
| Standard Taper Curve Per Section:                                   |
| A single section  |

## NSN 5905-00-368-8977

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



| Terminal Type And Quantity: |
|-----------------------------|
| 3 tab, solder lug           |
| Shelf Life:                 |
| N/a                         |
| Unit Of Measure:            |
|                             |
| Demilitarization:           |
| No                          |
| Fiig:                       |

A002a0