NSN 5905-00-368-8978

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-368-8978

Section Quantity:
1
Body Style: Cylindrical bushing mounted
Reliability Indicator:
Not established
Overall Length:
25.000 millimeters
Body Diameter: 20.000 millimeters
Shaft Diameter:
6.000 millimeters
Shaft Length: 15.000 millimeters
Body Length: 10.000 millimeters
Overall Diameter:
25.800 millimeters
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Nonturn Device Location:
At 9 oclock
Nonturn Device Radius:
7.500 millimeters
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Locking bushing
Features Provided:
Nonmetallic shaft
Electrical Resistance Per Section:
150.0 kilohms single section
Power Dissipation Rating Per Section In Watts:
0.25 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
50.0 single section
Standard Taper Curve Per Section:

A single section

NSN 5905-00-368-8978

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0