Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-369-0930

Section Quantity:

1

Body Style:

Rectangular w/mounting holes/slots

Reliability Indicator:

Not established

Overall Length:

2.094 inches

Terminal Length:

0.188 inches

Overall Height:

1.188 inches

Overall Width:

0.062 inches

Mounting Hole Diameter:

0.078 inches

Shaft Diameter:

0.078 inches

Shaft Length:

0.094 inches

Body Length:

2.000 inches

Body Width:

0.062 inches

Body Height:

1.000 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

360.0

Center To Center Distance Between Terminals:

0.200 inches

Lateral Distance Between Mounting Hole Centers:

1.750 inches

Mounting Facility Quantity:

2

Terminal Location:

Lower adjacent side two rows

Mounting Method:

Terminal and unthreaded hole



Center To Center Distance Between Terminal Rows: 0.100 inches **Features Provided:** Nonmetallic shaft **Electrical Resistance Per Section:** 1.6 kilohms single section **Rotary Actuator Travel In Angular Deg:** 360.0 Center To Center Distance Between Center Terminal And Outside Terminal: 0.100 inches Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 105.0 single section **Power Dissipation Rating Per Section In Watts:** 25.0 free air single section **Resistance Tolerance Per Section In Percent:** -1.0 to 1.0 single section **Actuator Travel Control Feature:** Continuous motion Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section Standard Taper Curve Per Section: A single section **Terminal Type And Quantity:** 3 pin Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A002a0