Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-369-1034

# Section Quantity:

1

Body Style:

Rectangular

# **Reliability Indicator:**

Not established

#### **Terminal Length:**

0.188 inches

#### Shaft Diameter:

0.075 inches

#### Shaft Length:

0.040 inches

#### Body Length:

0.500 inches

#### Body Width:

0.100 inches

# Body Height:

0.150 inches

# Shaft Style:

Round, slotted

# Actuator Type:

Single shaft

#### Effective Electrical Rotation In Deg Angular Rotation:

2880.0

#### **Center To Center Distance Between Terminals:**

0.300 inches

#### **Terminal Location:**

Lower adjacent side single row

#### **Mounting Method:**

Terminal

#### **Electrical Resistance Per Section:**

10.0 kilohms single section

#### **Rotary Actuator Travel In Angular Deg:**

2880.0

#### Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

## Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

## Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0 to 100.0 single section

# Power Dissipation Rating Per Section In Watts:

0.3 free air single section



**Resistance Tolerance Per Section In Percent:** 

-10.0 to 10.0 single section

### Actuator Travel Control Feature:

Clutch

## Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0