## NSN 5905-00-371-8265

**Section Quantity:** 

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-371-8265

1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Overall Length:
3.814 inches
Body Diameter:
0.875 inches
Shaft Diameter:
Between 0.124 inches and 0.125 inches
Shaft Length:
0.438 inches
Mounting Bushing Length:
0.438 inches
Body Length:
2.938 inches
Overall Diameter:
1.045 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
7200.0
Maximum Starting Torque:
3.00 inch-ounces
Maximum Running Torque:
3.00 inch-ounces
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Longitudinally positioned on the circumference
Mounting Method:
Shaft w/panel seal and standard bushing
Features Provided:
Nonmetallic shaft

## NSN 5905-00-371-8265

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:
50.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
7200.0
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Actuator Travel Control Feature:
Stops
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0