NSN 5905-00-372-0037

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-372-0037

Electrical Resistance: 22.900 kilohms Resistance Tolerance In Percent: -0.100/4-0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 1475.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Inclosu	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
22.900 kilohms Resistance Tolerance In Percent: -0.100/4-0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0/+175.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: -5stablished Reliability Failure Rate Level In Percent: -0.001 Body Diameter: -0.125 inches Body Length: -0.375 inches Power Dissipation Rating In Watts: -0.126 free air Style Designator:	-25.0/+25.0
Resistance Tolerance In Percent: -0.100/4-0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -0.55.0/+175.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: -0.001 Body Diameter: -0.125 inches Body Length: -0.375 inches Power Dissipation Rating In Watts: -0.125 free air Style Designator: Axial terminal each end Test Data Document: Bi349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: No	Electrical Resistance:
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.125 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: Bri349-milt55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a	22.900 kilohms
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: -0.001 Body Diameter: -0.125 inches Body Length: -0.375 inches Power Dissipation Rating In Watts: -0.125 free air Style Designator: Axial terminal each end Test Data Document: B1349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Established Reliability Indicator: 151.0001 Body Diameter: 10.125 inches	-0.100/+0.100
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.125 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 81349-milit55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a	Ambient Tempurature In Deg Celsius At Full Rated Power:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+175.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Boddy Diameter: 0.125 inches Boddy Length: 0.375 inches Power Dissipation Rating In Watts: 0.126 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a	125.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: 1-55.0/+175.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.125 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.125 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: B1349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a	175.0
Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.125 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.125 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a	-55.0/+175.0
Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.125 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a	Inclosure Method:
Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.125 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: B1349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a	Hermetically sealed
Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.125 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: B1349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a	Terminal Type:
Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.125 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a	Wire lead
Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.125 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a	Reliability Indicator:
Body Diameter: 0.125 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a	Established
Body Diameter: 0.125 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a	Reliability Failure Rate Level In Percent:
0.125 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: B1349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a	0.001
Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a	Body Diameter:
D.375 inches Power Dissipation Rating In Watts: D.125 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life:	0.125 inches
Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life:	Body Length:
O.125 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life:	0.375 inches
Style Designator: Axial terminal each end Test Data Document: 81349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life:	Power Dissipation Rating In Watts:
Axial terminal each end Test Data Document: 81349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life:	0.125 free air
Test Data Document: 81349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life:	Style Designator:
81349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a	Axial terminal each end
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a	Test Data Document:
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a	81349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
Shelf Life:	format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
N/a	environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
	Shelf Life:
Unit Of Measure:	N/a
	Unit Of Measure:
	
Demilitarization:	Demilitarization:
No	No
Fiig:	Fiig:
A001a0	A001a0